

DISHES

Satellite dishes manufactured of electro zinc-coated steel with a polyester coating ensuring high level of resistance to weather conditions.

APPLICATION

Suitable for community and individual Satellite TV installations. Available a wide range of diameters according to the size of the installation.

CHARACTERISTICS

- The parabolic reflectors are designed to achieve high gain.
- Pole or wall mounting.



SIGNAL
RECEPTION

MODEL		PO 064	PO 081	DPO 105*
Reference		86064	86081	86105
Diameter	cm	51 x 57	73 x 80	91 x 100
Focal distance	cm	32,7	46,8	58,3
Type of reflector		Offset		
Material		Electro zinc-coated steel		
Coating		Polyester		
Type of fixing		Floor / Wall / Pole		Mast
Mast diameter	mm	30 ÷ 60	30 ÷ 60	30 ÷ 60
Elevation	°	17 ÷ 55	17 ÷ 55	- 5 ÷ 82
Offset angle	°	19		
Azimuth	°	180		
LNB fixing Ø	mm	25 ÷ 40		
Frequency range	GHz	10 ÷ 12,75		
Gain (11,7 Ghz)	dB	35	38	39,2
Efficiency	%	>60		
Beam width (- 3 dB)	°	2,8	2,4	2,1
F/D relation		0,64		
Wind speed		Operating: up to 100 km/h Maximum: up to 130 km/h		
Packing dimensions	mm	610 x 610 x 110	830 x 840 x 120	1020 x 1000 x 120
Weight	Kg	5	9	10

* Pole not included. See accessories.