

- E** DIPLEXOR BLINDADO
GB SHIELDED DIPLEXER



DXR 216/DXR 334

E	GB		DXR 216	DXR 334
Referencia	Reference		86245	86334
Nº entradas	Number of inputs		2	3
Nº salidas	Number of outputs		1	1
Paso DC SAT IN -OUT	DC Pass SAT IN-OUT		500 mA, max	—
Entrada SAT IN	Input SAT IN	MHz	950÷2300	—
Entrada RF IN	Input RF IN split-band	MHz	15÷862	15÷230, 470÷862
Entrada RF IN (-12 dB)	Input RF IN (-12 dB) broadband	MHz	—	15÷862
Entrada HYP IN	Input HYP IN (m)	MHz	—	300÷420
Salida OUTN	Output OUT	MHz	15÷2300 MHz	15÷862
Pérdidas de paso SAT IN	Through Loss SAT IN	dB	2±1	—
Pérdidas de paso RF IN	Through Loss RF IN	dB	<2	2 (862 MHz)
Pérdidas de paso RF IN (-12 dB)	Through Loss RF IN (-12 dB)	dB	—	12 (15÷862 MHz)
Pérdidas de paso HYP IN	Through Loss HYP IN	dB	—	3 (300÷420 MHz)
Pérdidas de retorno OUT	Output Return losses	dB	6	6
Rechazo SAT IN	Reject SAT IN	dB	>36 (47÷862 MHz)	—
Rechazo RF IN	Reject RF IN	dB	> 13 (950 MHz) > 30 (1200÷2300 MHz)	30 (300÷420 MHz)
Dimensiones de embalaje (8 unidades)	Packing dimensions (8 u.)	mm	115 x 110 x 47	115 x 110 x 47
Peso (8 unidades)	Weight (8 u.)	Kg	0,95	0,95

Fagor Electrónica, S.Coop.

San Andrés, s/n.
E-20500 Mondragón (Spain)
Tel. +34 43 712526
Fax +34 43 712893
E-mail: rf.sales@fagorelectronica.es
www.fagorelectronica.com

